



MATERIAL SAFETY DATA SHEET

SSN200 CHIRAL SCREEN INK

Page 1 of 3
MSDS054 Revision 0
Revision date 3/20/2009

1. PRODUCT AND COMPANY IDENTIFICATION

Product name SSN200 CHIRAL SCREEN INK
Description Aqueous based ink containing acrylic resins.
Company LCR Hallcrest
1820 Pickwick Lane
Glenview
IL 60026
Telephone +1 847 998 8580
Fax +1 847 998 6866
Emergency telephone number +1 847 998 8580
Intended use Temperature measurement and thermal mapping.

2 HAZARDS IDENTIFICATION.

Statement of Hazard
Properties Color Tan.
Odor Mild
State Liquid
Main hazards Irritating to eyes and skin.

3 . COMPOSITION / INFORMATION ON INGREDIENTS.

Hazardous ingredients

	Conc.	CAS
CHIRAL NEMATIC LIQUID CRYSTAL	20 - 30%	

4. FIRST AID MEASURES

Skin contact May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Eye contact May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Inhalation May cause irritation to mucous membranes. Move the exposed person to fresh air.
Ingestion May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

5. FIRE FIGHTING MEASURES

Extinguishing media Use extinguishing media appropriate to the surrounding fire conditions.
Fire hazards Burning produces irritating, toxic and obnoxious fumes.
Protective equipment Wear suitable respiratory equipment when necessary.

SSN200 CHIRAL SCREEN INK

Page 2 of 3
MSDS054 Revision 0
Revision date 3/20/2009

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Ensure adequate ventilation of the working area.
Environmental precautions	Do not allow product to enter drains. Prevent further spillage if safe.
Clean up methods	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labeled containers for disposal. Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
Storage	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labeled containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures	Ensure adequate ventilation of the working area.
Hand protection	Chemical resistant gloves (PVC)
Eye protection	In case of splashing, wear: Approved safety goggles.
Protective equipment	Wear protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description	Liquid.
Color	Tan.
Odor	Mild.
pH	4-6
Boiling point	100°C
Flammability limits	N/A
Viscosity	1200 CPS

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
------------------	---------------------------------

11. TOXICOLOGICAL INFORMATION

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

General information	Dispose of in compliance with all local and national regulations.
----------------------------	---

14. TRANSPORT INFORMATION

Further information	The product is not classified as dangerous for carriage.
----------------------------	--

15. REGULATORY INFORMATION

SSN200 CHIRAL SCREEN INK

Page 3 of 3
MSDS054 Revision 0
Revision date 3/20/2009

16. OTHER INFORMATION

Statement of Hazard

Further Information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.

TSCA

All components are TSCA compliant.

HMIS LABELLING

HEALTH 1, FLAMMABILITY 0, PHYSICAL HAZARD 0 PERSONAL PROTECTION :
C.