

## CHILLCHECKER

A cost effective solution to identify temperature control issues during temperature sensitive product transportation and storage.

<b>TYPE:</b>	Chill Checker Indicator, Circular, Self-Adhesive
<b>SIZE:</b>	32mm diameter by 6mm deep (1.25" by 0.23" deep)
<b>PRINT:</b>	2 Colors: Blue Print onto White Background
<b>EVENTS:</b>	1
<b>ACCURACY:</b>	+/-1°C
<b>TEMPERATURE:</b>	in °F and °C,
<b>PACKAGING:</b>	Packs of 10

Product	1:	-17°C/+1°F
	2:	-8°C/+18°F
	3:	-5°C/+23°F
	4:	-2°C/+28°F
	5:	+5°C/+41°F
	6:	+9°C/+48°F
	7:	+17°C/+63°F
	8:	+20°C/+68°F

### • Instruction for Use

1. Remove silicone release paper and apply firmly to surface of product to be monitored to subject being measured.
2. Cool below specified rating for at least 60 minutes before activating.
3. To activate push the center of the convex surface until it becomes concave.

**Note:** Chill Checkers should be ideally stored below their temperature rating at all times and if this is done they can be removed from cold store, placed onto a pre chilled product directly and activated. If product is not chilled then the unit may activate

### **Indication**

Staining of the white paper occurs after a short period of time (not exceeding 5 minutes) when the temperature rating is exceeded. The longer the period that the temperature is above its rating the further the staining will spread.

If the temperature then drops below its rating staining will be halted, however, if temperature increases again then staining will recommence. The effect is therefore cumulative.